

Technical Data Sheet

CS110 - Clear Spray Grade Contact Adhesive



DESCRIPTION:

Lockfast CS110 is a versatile, sprayable, solvent based contact adhesive.
CS110 is suitable for bonding varying materials to themselves and substrates.

RECOMMENDED USES:

- Metal Foils
- Commercial Flooring Vinyl
- Plastic laminates to themselves or to timber or particle board
- Polyurethane Foams
- Carpets
- Timber veneers

LIMITATIONS:

- CS110 is not suitable for expanded polystyrene foams.
- Always test a small area of the particular materials to be bonded to evaluate the suitability of the adhesive to both material and substrate.
- Staining is possible on some materials

PERFORMANCE DATA:

Element	Value
Minimum Application Temperature: Air	+10°C
Maximum Application Relative Humidity: Air	80%
Flash Point:	-22°C
Adhesion Properties to correctly prepared surface:	~ Fabrics ~ Metal ~ Timbers Excellent Excellent Excellent
Type:	Sprayable Contact Adhesive
Base:	Polychloroprene Rubber / Resin
Adhesive Solids:	18 – 22%
SG kg/litre:	0.85
Colour:	Natural (Honey Coloured)
Coverage:	Approximately 6m ² per litre /per surface (3m ² of bonded area per litre)
Open Time:	+25°C –50%RH 1 – 10 minutes (depending on porosity of materials and ambient temperature).
Clean Up:	Solvent HA
Dangerous Goods Class:	Refer SDS
Packaging:	20 litre Pail
Shelf life:	6 months from date of manufacture in unopened containers at 5 -30°C.

SURFACE PREPARATION:

It is essential that the surfaces to be bonded are dry and clean.
All traces of dust, oil and dirt must be removed; it may be necessary to wipe surfaces with Solvent HA.

MIXING METHOD:

Stir adhesive thoroughly before using. A small amount only of Lockfast Solvent HA may be added to thin if necessary.

APPLICATION METHOD:

Spray | Roller | Brush

For good results, the temperature of the adhesive and materials to be bonded should be above +10°C with relative humidity below 80%.

CAUTION:

The rapid drying of the solvent in cold/damp conditions may cause blooming (water condensation on the surface – a whitening effect). This will affect adhesion. Improve forced air ventilation or warm the area or wait until the blooming dissipates.

- Apply a uniform coat of adhesive on **both surfaces** to be bonded.
- Allow adhesive to dry until it feels slightly tacky to the touch.
(This will take 1 – 10 minutes depending on porosity of materials and ambient temperature).
- On porous surfaces (e.g. edges of particle board), it is desirable to apply a second coat of adhesive.
- Once the adhesive has dried to the slightly tacky stage, the materials may be joined immediately or up to 30 minutes later.
- Accurately position the surfaces to be bonded then bring the coated surfaces together with smooth, firm pressure.
- Final bond strength will be obtained after 48 hours.
- Rolling with a square edge or round edge heavy hand roller will dramatically improve adhesion.

HEALTH & SAFETY: Refer safety data sheets (SDS).

- Wear appropriate safety equipment and clothing
- Contains potentially strong solvents (toluene, ketones, and aliphatic hydrocarbons). Breathing of vapour should be avoided.
- Use organic vapour masks; particularly in confined spaces.
- The use of fans to provide positive forced air draft and/or extraction is recommended.
- Do not use CS110 near naked flames, electric heaters, electric motors or other sources of ignition such as gas pilot lights.
- Avoid skin contact.

ADHESIVE RANGE:**Solvent-based**

Product	Type	Colour	Application Method	Installation Type
CB103	Brushable Contact	Straw	Brush Roller	Various – Refer Technical Literature
CS110	Sprayable Contact	Straw	Brush Roller Spray	Various – Refer Technical Literature
CS107	Sprayable Contact	Red	Brush Roller Spray	Various – Refer Technical Literature
Quicktack	Trowel Grade	Cream	Trowel	Garage & Outdoor Carpet

Water-based

Product	Type	Colour	Application Method	Installation Type
Duracryl HSV	Acrylic	Off-white	Trowel	Vinyl – all types Vinyl Planks* ¹
Supacryl	Acrylic - Zero VOC	White	Trowel	Vinyl – all types Vinyl Planks
Truestik VA1	Acrylic - Zero VOC	Off-white	Trowel	Vinyl – all types Vinyl Planks
Supatack T9 -Gen 2	Acrylic	Off-white	Trowel	Vinyl – all types Vinyl Planks
Goldstix	Latex-based	Off-white	Trowel	Carpet
RMA 2000 CTA	Acrylic	Pink	Trowel Roller	Carpet Tiles Polystyrene
Super 7	Acrylic	Off-white	Trowel	Rigid Vinyl Tiles Direct Stick Carpet Underlay

Epoxy | Polyurethane

Product	Type	Colour	Application Method	Installation Type
NPU	2-part Polyurethane	Beige	Trowel	Various – Refer Technical Literature
Truestik EA	2-part Epoxy	Green	Trowel	Various – Refer Technical Literature* ²

*1 Recommended adhesive for vinyl plank

*2 Recommended adhesive for vinyl planks in areas exposed to solar heat gain.

Date: Sept 2021

Replaces: Oct 2019

Allnex Construction Products, a Division of Allnex New Zealand Ltd

Auckland - 14 Industry Road, Penrose, phone: 09-583-6544.

Hamilton - 18 Somerset Street, Frankton, phone: 07-847-8658.

Wellington - Unit 9A \$ Glover Street, Ngauranga, Gorge phone: 04-240-0305.

Christchurch - 112 Carlyle Street, Sydenham, phone: 03-366-6802.

Customer Service: 0508-882-288 cs.constructionnz@allnex.com

www.allnexconstruction.com



DISCLAIMER: This information appearing in this Document (**Details**) concerning the product which is the subject of the Document (**Product**) is either based on present technical knowledge and tests done by allnex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of allnex, no warranty or representation, express or implied is made by allnex regarding the suitability for such use, nor does allnex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. allnex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, allnex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against allnex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. allnex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of allnex which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree: a.) The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. b.) The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. c.) Where the Details relate to Product tested by allnex, those Details are indicative only, regarding which there may be batch to batch variation. d.) allnex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. e.) allnex's liability for breach of any term, condition, guarantee or warranty (express or implied) and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at allnex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.