

Technical Data Sheet

Epoxy Coving Resin



DESCRIPTION:

Epoxy Coving Resin is a thix'd epoxy designed for use with the Supascreed industrial grade resin floor topping system. Epoxy Coving Resin has been specifically blended to produce a gelled structure to use as an adhesion promoter when installing Supascreed Coving. Epoxy Coving Resin may also be mixed in with the Supascreed Cove mix if required.

TYPICAL FEATURES | BENEFITS:

- Low Odour.
- May be used in food safe areas.
- Cured Film is non-toxic
- HACCP approved manufacturing process as part of the Supascreed Resin Floor Topping System.
- Will not support bacteria or fungal growth. Contains inhibitors to retard microbial growth.
- Non-flammable.
- Excellent adhesion to properly prepared substrates.
- Not moisture permeable.

PERFORMANCE DATA AND PRODUCT PROPERTIES:

Properties	Values
Pot-Life:	+20°C ~50%RH 45 minutes
Hard Dry:	+20°C ~50%RH Standard Hardener: 24 hours
Minimum Application Temperature:	+5°C
Maximum Application Relative Humidity: Air	85%
Recoat:	Anytime within 24 hours. <i>After 24 hours: Severe mechanical abrasion</i>
Thinning:	NA
Clean Up: ~ Tools	Allnex Acetone
Dangerous Good Class: ~ Epoxy Coving Resin ~ Epoxy Coving Hardener	Refer SDS
Packaging ~ Epoxy Coving Resin ~ Epoxy Coving Hardener	20kg - Open Top Pail 6.7 kg - Open Top Pail
Shelf life:	6 months from date of manufacture (After this period consult with allnex)

RECOMMENDED USES:

- Adhesion promoter when installing Supascreed or other epoxy coving.
- Epoxy Coving Resin may also be mixed in with the Supascreed Cove mix if required.
- Filling of small divots in concrete substrates prior to the installation of "Coating systems".

LIMITATIONS:

- Application to uncured concrete (minimum recommended cure 28 days). Tolerant of damp surfaces. (*Refer to allnex Bulletin on application options on wet or uncured*)
- Application to unstable or defective substrates without approved remedial treatment prior to installation.
- Application below +5°C.

SUBSTRATE: – Preparation

All substrates shall be stable and solid and prepared in accordance with the requirements of the substrate. All Substrates must be primed with Supascreed Primer.

QUALITY ASSURANCE:

The allnex Licensed Contractor shall ensure all QA checks have been undertaken prior to the installation process and subsequently during the installation process as part of the requirement for the Supascreed resin floor topping system.

PREPARATION: - Primer Installation

- Prime the correctly prepared area with minimum, one coat of Supascreed Primer.
- Coverage rate and number of coats will vary depending on the porosity of the substrate,
- Maximum coverage 6m²/litre/coat. Supascreed Primer Resin and Hardener are to be thoroughly mixed in the correct proportions and then diluted with clean potable water and remixed.
- Wait until Supascreed Primer has turned clear before over-coating.

EPOXY COVING RESIN APPLICATION:

EPOXY COVING RESIN MIXING RATIO:

Epoxy Coving Resin Mixing Ratio	
Epoxy Coving Resin	3 parts by weight
Epoxy Coving Hardener	1 part by weight

- Mix Coving Resin to a streak free homogenous mix and apply allnex Coving Resin to the correctly prepared and sealed substrate.
- Epoxy Coving Resin is applied by brush.

Note

Maximum coverage 3m²/litre

- Subsequently; Supascreed Coving is then applied ensuring the matrix is well compacted and free of ridges or unevenness.

HEALTH & SAFETY: Refer safety data sheets (SDS).

- Wear appropriate safety equipment and clothing
- The use of fans to provide positive forced air draft and/or extraction is recommended.
- Avoid skin contact.

Date: March 2022
Replaces: Oct 2020

Allnex Construction Products, a Division of Allnex New Zealand Ltd
Auckland - 14 Industry Road, Penrose, phone: 09-583-6544.
Hamilton - 18 Somerset Street, Frankton, phone: 07-847-8658
Wellington - Unit 9A 4 Glover Street, Ngauranga Gorge, phone: 04-240-0305.
Christchurch - 112 Carlyle Street, Sydenham, phone: 03-366-6802.
Customer Service: 0508-882-288 cs.constructionnz@allnex.com
www.allnexconstruction.com

DISCLAIMER: This information appearing in this Document (Details) concerning the product which is the subject of the Document (Product) is either based on present technical knowledge and tests done by allnex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of allnex, no warranty or representation, express or implied is made by allnex regarding the suitability for such use, nor does allnex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. allnex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, allnex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against allnex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. allnex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of allnex which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree: a.) The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. b.) The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. c.) Where the Details relate to Product tested by allnex, those Details are indicative only, regarding which there may be batch variation. d.) allnex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. e.) allnex's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at allnex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.