

# Technical Data Sheet

## BITUTHENE PRIMER TYPE C



### Description

A liquid membrane curing compound and primer for BITUTHENE® membranes. It consists of water dispersed non-volatile solids. After application, the water evaporates leaving a thin impermeable film over the surface.

### Uses

BITUTHENE® Primer Type C is designed for concrete, brick and masonry substrates to which any BITUTHENE® self-adhesive sheet membrane will be applied. It is also a Class 3 Type Z curing blanket for freshly placed concrete.

### Features

- Complies with Green Star requirements
- It facilitates moisture retention in the concrete giving maximum strength and durability.
- Based on a fine particle bitumen emulsion to give a tenacious, vapour proof bond to the substrate.
- Certified curing compound to AS3799:1998.
- Non-hazardous – no VOC
- Quick drying and low odour

### Preparation

Surfaces must be sound clean, free from dust, oil, grease or contaminants. Do not apply when rain is expected.

### Application

Mix thoroughly immediately prior to use and agitate product during application.

Apply one full coat forming a continuous film at a rate of 5m<sup>2</sup> / L by brush, broom, roller or low pressure spray. Allow to dry and apply the BITUTHENE® waterproof membrane in accordance with manufacturer's instructions.

### Typical Properties

Colour	Black
S.G.	0.95 – 1.0g / ml
Viscosity	>0.050Pa.s
Water Retention (AS3799.3.1.2)	90%
Drying Time @ 25°C	1½ - 2 hours
VOC	0%

If using as curing compound, apply a further coat after a minimum 7 days cure. Early application of membrane may increase moisture vapour bubbles under BITUTHENE®.

### Compatibility

BITUTHENE® Primer Type C is designed for use under all Bituthene waterproof membrane systems.

### Coverage

BITUTHENE® Primer Type C is ready to use straight from container. Application rate is 5 to 6m<sup>2</sup> / L using brush roller or spray application. Coverage may vary depending on ambient temperature, porosity and texture of surface.

### Packaging

Packed in 20 litre pails or 200 litre drums.

### Storage

Store pails in a cool dry place. Unopened containers have a shelf life of 12 months from the date of manufacture.

## Clean Up

Remove uncured product with water. GP Solvent or Kerosene will assist with the removal of cured product. Exercise care when using solvents. Please review all Materials Safety Data Sheet before use.



Date: July 2018  
Replaces August 2017

### Allnex Construction Products, a Division of Allnex New Zealand Ltd

Auckland - 14 Industry Road Penrose phone: 095836544. Hamilton - 18 Somerset Street Frankton phone: 07-847-8658  
Wellington - 19A Jamaica Drive Grenada North phone: 04-240-0305. Christchurch - 112 Carlyle Street Sydenham phone: 03-366-6802  
Customer Service: 0508-882-288 [cs.constructionnz@allnex.com](mailto:cs.constructionnz@allnex.com)  
[www.allnexconstruction.com](http://www.allnexconstruction.com)

The allnex logo, consisting of the word "allnex" in a bold, lowercase, sans-serif font. Above the letters "l", "n", and "x" are horizontal bars in purple, red, and green respectively.

**DISCLAIMER:** This information appearing in this Document (**Details**) concerning the product which is the subject of the Document (**Product**) is either based on present technical knowledge and tests done by allnex or tests done by, and data supplied from third parties including you, the customer. Since the actual use by you and by others of the Product is beyond the control of allnex, no warranty or representation, express or implied is made by allnex regarding the suitability for such use, nor does allnex accept any liability arising out of the use by you of other products or materials, whether third party or not, that may be referred to in this Document. allnex recommends that you carry out your own tests as to the suitability of the Product for your purpose, regarding which you accept full responsibility. In addition, if any of the Details appearing in the Document are based upon tests done by, and/or data supplied by any third party, allnex provides no warranties or representations in connection with those Details and you, the customer waives any right you may have against allnex in connection with the accuracy, completeness or otherwise of the Details. The information in this Document is not to be construed as absolutely complete or accurate since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations affecting use of the Product. allnex does not provide any warranty or representation to you that the Product does not infringe the intellectual property rights of any third party. All orders accepted shall be subject to the standard conditions of sale of allnex which are on the back of our invoice. In accepting the Product you, the customer acknowledge and agree: **a.)** The Product is or may be of a hazardous nature and that you, the customer, are responsible for the disposal of the container housing the Product in accordance with the requirements and regulations of the relevant supervising government. **b.)** The Product has a limited shelf life and must be stored strictly in accordance with the guidelines and specifications related to it. **c.)** Where the Details relate to Product tested by allnex, those Details are indicative only, regarding which there may be batch to batch variation. **d.)** allnex gives no warranty or representation as to the applicability for the particular use by you, the customer, of the Product and you the customer shall be responsible for ensuring that the Product is fit for your intended use. **e.)** allnex's liability for breach of any term, condition, guarantee or warranty (express or implied and concerning the information in this Document or the Product more generally) including any liability for direct or indirect consequential loss (including indirect loss of profits), is limited to the maximum extent permitted by law and, at allnex's election, to either replacing or repairing the goods or paying the cost of replacing or repairing the goods, or in the case of services, supplying the services again.